

Malleable Iron Die Cast - Threaded - "LB" Type

Industry Standards

- UL 514A
- Federal Spec W-c 586D
- NEMA – FB-1

Construction


- Body – Malleable Iron
- Finish – Zinc Plating with Aluminum Enamel Paint

Application

- To provide access for electrical conductors when pulling, splicing and/or maintenance

Features

- Tapered Threaded Hubs-NPT
- Suitable for concrete and wet locations



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)		
					A	B	C
AI MLB 050	½"	10	0.71	7.1	4 ¹¹ / ₁₆ "	1 ⁵ / ₁₆ "	2 ¹ / ₁₆ "
AI MLB 075	¾"	10	0.97	9.7	5 ³ / ₈ "	1½"	2¼"
AI MLB 100	1"	5	1.4	7	6 ³ / ₁₆ "	2"	2 ⁵ / ₈ "
AI MLB 125	1¼"	2	2.9	14.5	8 ¹ / ₈ "	2 ⁵ / ₈ "	2¾"
AI MLB 150	1½"	2	3.3	6.6	8 ¹ / ₈ "	2 ⁵ / ₈ "	2 ¹³ / ₁₆ "
AI MLB 200	2"	1	5.3	5.3	10½"	3 ³ / ₈ "	4 ⁷ / ₁₆ "
AI MLB 250	2½"	1	11	11	13 ⁵ / ₈ "	4 ⁵ / ₁₆ "	5 ³ / ₈ "
AI MLB 300	3"	1	11.6	11.6	13 ³ / ₈ "	4 ⁵ / ₁₆ "	5 ¹ / ₈ "
AI MLB 350	3½"	1	19.9	19.9	16¼"	5 ⁵ / ₈ "	6 ⁷ / ₈ "
AI MLB 400	4"	1	21	21	16 ⁵ / ₈ "	5 ⁵ / ₈ "	7 ³ / ₁₆ "

Malleable Iron Die Cast - Threaded - "LL" Type

Industry Standards

- UL 514A
- Federal Spec W-c 586D
- NEMA – FB-1

Construction


- Body – Malleable Iron
- Finish – Zinc Plating with Aluminum Enamel Paint

Application

- To provide access for electrical conductors when pulling, splicing and/or maintenance

Features

- Tapered Threaded Hubs-NPT
- Suitable for concrete and wet locations



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)		
					A	B	C
AI MLL 050	½"	10	0.76	7.6	4 ¹¹ / ₁₆ "	2 ¹ / ₁₆ "	1 ³ / ₈ "
AI MLL 075	¾"	10	0.95	9.5	5 ³ / ₈ "	2¼"	1 ¹¹ / ₁₆ "
AI MLL 100	1"	5	1.9	9.5	6 ³ / ₁₆ "	2 ⁵ / ₈ "	1 ¹ / ₈ "
AI MLL 125	1¼"	2	3.1	6.2	8 ¹ / ₈ "	2¾"	2¾"
AI MLL 150	1½"	2	3.3	6.6	8 ¹ / ₈ "	3½"	2 ¹³ / ₁₆ "
AI MLL 200	2"	1	5	5	10½"	4 ¹ / ₈ "	3 ⁵ / ₁₆ "
AI MLL 250	2½"	1	11.1	11.1	13 ⁵ / ₈ "	4 ¹¹ / ₁₆ "	3 ⁷ / ₈ "
AI MLL 300	3"	1	15.4	15.4	13 ⁷ / ₈ "	5 ¹ / ₈ "	4¾"
AI MLL 350	3½"	1	23.2	23.2	16¼"	6 ¹ / ₈ "	5 ⁵ / ₈ "
AI MLL 400	4"	1	24.3	24.3	16¼"	5 ¹⁵ / ₁₆ "	5 ⁵ / ₈ "

Malleable Iron Die Cast - Threaded - "LR" Type

Industry Standards

- UL 514A
- Federal Spec W-c 586D
- NEMA – FB-1

Construction

- Body – Malleable Iron
- Finish – Zinc Plating with Aluminum Enamel Paint

Application

- To provide access for electrical conductors when pulling, splicing and/or maintenance

Features

- Tapered Threaded Hubs-NPT
- Suitable for concrete and wet locations



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)		
					A	B	C
AI MLR 050	½"	10	0.71	7.1	4 ¹¹ / ₁₆ "	2 ¹ / ₁₆ "	1 ³ / ₈ "
AI MLR 075	¾"	10	1	10	5 ³ / ₈ "	2¼"	1 ¹¹ / ₁₆ "
AI MLR 100	1"	5	1.6	8	6 ³ / ₁₆ "	2 ⁵ / ₈ "	1 ¹ / ₈ "
AI MLR 125	1¼"	2	3.3	6.6	8 ¹ / ₈ "	2¾"	2¾"
AI MLR 150	1½"	2	3.5	7	8 ¹ / ₈ "	2 ¹³ / ₁₆ "	2 ¹³ / ₁₆ "
AI MLR 200	2"	1	6.3	6.3	10½"	4 ⁷ / ₁₆ "	3 ⁵ / ₁₆ "
AI MLR 250	2½"	1	11.1	11.1	13 ⁵ / ₈ "	5 ³ / ₈ "	3 ⁷ / ₈ "
AI MLR 300	3"	1	14.4	14.4	13 ⁷ / ₈ "	5 ¹ / ₈ "	4¾"
AI MLR 350	3½"	1	23.2	23.2	16¼"	6 ¹ / ₈ "	5 ⁵ / ₈ "
AI MLR 400	4"	1	25	25	16 ⁵ / ₈ "	7 ³ / ₁₆ "	5 ⁵ / ₈ "