

## Malleable Iron Die Cast - Threaded - "LB" Type

### Industry Standards

- UL 514A
- Federal Spec W-c 586D
- NEMA – FB-1

### Construction


- Body – Malleable Iron
- Finish – Zinc Plating with Aluminum Enamel Paint

### Application

- To provide access for electrical conductors when pulling, splicing and/or maintenance

### Features

- Tapered Threaded Hubs-NPT
- Suitable for concrete and wet locations



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)		
					A	B	C
AI MLB 050	1/2"	10	0.71	7.1	4-11/16	1-5/16	2-1/16
AI MLB 075	3/4"	10	0.97	9.7	5-3/8	1-1/2	2-1/4
AI MLB 100	1"	5	1.4	7	6-3/16	2	2-5/8
AI MLB 125	1 1/4"	2	2.9	14.5	8-1/8	2-5/8	2-3/4
AI MLB 150	1 1/2"	2	3.3	6.6	8-1/8	2-5/8	2-13/16
AI MLB 200	2"	1	5.3	5.3	10-1/2	3-1/8	4-7/16
AI MLB 250	2 1/2"	1	11	11	13-5/8	4-5/16	5-3/8
AI MLB 300	3"	1	11.6	11.6	13-7/8	4-5/16	5-7/8
AI MLB 350	3 1/2"	1	19.9	19.9	16-1/4	5-5/8	6-7/8
AI MLB 400	4"	1	21	21	16-5/8	5-5/8	7-3/16

## Malleable Iron Die Cast - Threaded - "LL" Type

### Industry Standards

- UL 514A
- Federal Spec W-c 586D
- NEMA – FB-1

### Construction

- Body – Malleable Iron
- Finish – Zinc Plating with Aluminum Enamel Paint

### Application

- To provide access for electrical conductors when pulling, splicing and/or maintenance

### Features

- Tapered Threaded Hubs-NPT
- Suitable for concrete and wet locations



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)		
					A	B	C
AI MLL 050	1/2"	10	0.76	7.6	4-11/16	2-1/16	1-3/8
AI MLL 075	3/4"	10	0.95	9.5	5-3/8	2-1/4	1-11/16
AI MLL 100	1"	5	1.9	9.5	6-3/16	2-5/8	1-7/8
AI MLL 125	1 1/4"	2	3.1	6.2	8-1/8	2-3/4	2-3/4
AI MLL 150	1 1/2"	2	3.3	6.6	8-1/8	3-1/2	2-13/16
AI MLL 200	2"	1	5	5	10-1/2	4-1/8	3-5/16
AI MLL 250	2 1/2"	1	11.1	11.1	13-5/8	4-11/16	3-7/8
AI MLL 300	3"	1	15.4	15.4	13-7/8	5-7/8	4-3/4
AI MLL 350	3 1/2"	1	23.2	23.2	16-1/4	6-1/8	5-5/8
AI MLL 400	4"	1	24.3	24.3	16-1/4	5-15/16	5-5/8

## Malleable Iron Die Cast - Threaded - "LR" Type

### Industry Standards

- UL 514A
- Federal Spec W-c 586D
- NEMA – FB-1

### Construction

- Body – Malleable Iron
- Finish – Zinc Plating with Aluminum Enamel Paint

### Application

- To provide access for electrical conductors when pulling, splicing and/or maintenance

### Features

- Tapered Threaded Hubs-NPT
- Suitable for concrete and wet locations



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)		
					A	B	C
AI MLR 050	1/2"	10	0.71	7.1	4-11/16	2-1/16	1-3/8
AI MLR 075	3/4"	10	1	10	5-3/8	2-1/4	1-11/16
AI MLR 100	1"	5	1.6	8	6-3/16	2-5/8	1-7/8
AI MLR 125	1 1/4"	2	3.3	6.6	8-1/8	2-3/4	2-3/4
AI MLR 150	1 1/2"	2	3.5	7	8-1/8	2-13/16	2-13/16
AI MLR 200	2"	1	6.3	6.3	10-1/2	4-7/16	3-5/16
AI MLR 250	2 1/2"	1	11.1	11.1	13-5/8	5-3/8	3-7/8
AI MLR 300	3"	1	14.4	14.4	13-7/8	5-7/8	4-3/4
AI MLR 350	3 1/2"	1	23.2	23.2	16-1/4	6-7/8	5-5/8
AI MLR 400	4"	1	25	25	16-5/8	7-3/16	5-5/8