

Compression Type Rain-tight Connector

Industry Standards

- UL 514B
- Fed. Spec. W-F-408E
- NEMA FB-1

Construction

- Steel with Zinc Plated finish
- Steel Locknut
- Rubber Gasket

Application

- For use in joining EMT to box or metal enclosure
- Suitable for Outdoor use

Features

- Compression type connector
- Water tight and concrete tight assist to protect from environmental elements
- NPSM male hub threads



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)		
					A	B	C
AI MECR-750	1/2"	50	0.12	6.0	1.126	1.126	0.500
AI MECR-751	3/4"	25	0.17	4.3	1.376	1.376	0.501
AI MECR-752	1"	15	0.25	3.8	1.688	1.688	0.563
AI MECR-753	1-1/4"	20	0.48	9.6	2.063	2.063	1.013
AI MECR-754	1-1/2"	5	0.60	3.0	2.251	2.251	1.063
AI MECR-755	2"	10	1.00	10.0	2.751	2.751	1.126
AI MECR-756	2-1/2"	8	1.58	12.6	3.366	3.626	1.563
AI MECR-757	3"	4	2.50	10.0	4.251	4.251	1.563
AI MECR-758	3-1/2"	4	2.70	10.8	4.688	4.688	1.814
AI MECR-759	4"	4	3.50	14.0	5.189	5.188	1.814

Compression Type Rain-tight Connector with Insulated Throat

Industry Standards

- UL 514B
- Fed. Spec. W-F-408E
- NEMA FB-1

Construction


- Steel with Zinc Plated finish
- Steel Locknut
- Rubber Gasket
- Nylon Insulated throat

Application

- For use in joining EMT to box or metal enclosure
- Suitable for Outdoor use

Features

- Compression type connector
- Water tight and concrete tight assist to protect from environmental elements
- Insulated throat for added protection against abrasion
- NPSM male hub threads



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)		
					A	B	C
AI MECR-750-B	1/2"	50	0.12	6.0	1.126	1.126	0.500
AI MECR-751-B	3/4"	25	0.17	4.3	1.376	1.376	0.501
AI MECR-752-B	1"	15	0.25	3.8	1.688	1.688	0.563
AI MECR-753-B	1-1/4"	20	0.48	9.6	2.063	2.063	1.013
AI MECR-754-B	1-1/2"	5	0.60	3.0	2.251	2.251	1.063
AI MECR-755-B	2"	10	1.00	10.0	2.751	2.751	1.126
AI MECR-756-B	2-1/2"	8	1.58	12.6	3.366	3.626	1.563
AI MECR-757-B	3"	4	2.50	10.0	4.251	4.251	1.563
AI MECR-758-B	3-1/2"	4	2.70	10.8	4.688	4.688	1.814
AI MECR-759-B	4"	4	3.50	14.0	5.189	5.188	1.814

Compression Type Rain-tight Coupling

Industry Standards

- UL 514B
- Fed. Spec. W-F-408E
- NEMA FB-1

Construction


- Steel with Zinc Plated finish
- Nylon Compression Ring
- Steel Locknut

Application

- For use in joining two lengths of EMT
- Suitable for Outdoor use

Features

- Compression type coupling
- Water tight and concrete tight assist to protect from environmental elements



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI MECR-760	1/2"	50	0.14	7.00	1.626	1.126
AI MECR-761	3/4"	25	0.21	5.25	1.751	1.376
AI MECR-762	1"	15	0.29	4.35	1.876	1.688
AI MECR-763	1-1/4"	20	0.49	9.80	2.251	2.063
AI MECR-764	1-1/2"	5	0.60	3.00	2.251	2.251
AI MECR-765	2"	10	0.79	7.90	2.376	2.751
AI MECR-766	2-1/2"	8	2.05	16.40	3.876	3.626
AI MECR-767	3"	4	2.63	10.52	4.001	4.251
AI MECR-768	3-1/2"	4	3.09	12.36	4.688	4.688
AI MECR-769	4"	4	3.93	15.72	4.938	5.188