

## Two Hole EMT Strap - Snap On

### Industry Standards

- UL 2239

### Construction


- Steel with Zinc Plating

### Application

- Provides support to conduit where higher load bearing supports are required

### Features

- High corrosion resistance
- Inverted rib for additional strength



| catalog number | size in inches | box qty. | weight lbs. per unit | weight lbs. per box | dimensions (in.) |      |
|----------------|----------------|----------|----------------------|---------------------|------------------|------|
|                |                |          |                      |                     | A                | B    |
| AI 1124        | 1/2"           | 50       | 0.020                | 1.0                 | 2.21             | 0.58 |
| AI 1125        | 3/4"           | 50       | 0.030                | 1.5                 | 2.68             | 0.63 |
| AI 1126        | 1"             | 50       | 0.040                | 2.0                 | 2.98             | 0.76 |
| AI 1127        | 1-1/4"         | 20       | 0.060                | 1.2                 | 3.69             | 0.89 |
| AI 1128        | 1-1/2"         | 20       | 0.080                | 1.6                 | 4.23             | 1.00 |
| AI 1129        | 2"             | 50       | 0.140                | 7.0                 | 4.92             | 1.11 |

## Conduit Hanger with Nut and Bolt

### Industry Standards

- UL 2239

### Construction

- Steel with Zinc Plating

### Application

- To secure and suspend conduit (Rigid, IMC, EMT or PVC) from overhead support

### Features

- High corrosion resistance
- Furnished with carriage bolt



| catalog number | industry size | For EMT Diameter | bolt size  | box qty. | weight lbs. per unit | weight lbs. per box |
|----------------|---------------|------------------|------------|----------|----------------------|---------------------|
| AI 1/2-WBA     | 0             | 1/2"             | 1/4" - 20  | 100      | 0.06                 | 6.0                 |
| AI 3/4-WBA     | 1             | 3/4"             | 1/4" - 20  | 100      | 0.08                 | 8.0                 |
| AI 1-WBA       | 2             | 1"               | 1/4" - 20  | 100      | 0.09                 | 9.0                 |
| AI 1 1/4-WBA   | 2 1/2         | 1-1/4"           | 1/2" - 20  | 100      | 0.10                 | 10.0                |
| AI 1 1/2-WBA   | 3             | 1-1/2"           | 1/4" - 20  | 100      | 0.10                 | 10.0                |
| AI 2-WBA       | 5             | 2"               | 1/2" - 20  | 50       | 0.20                 | 10.0                |
| AI 2 1/2-WBA   | 6             | 2-1/2"           | 5/16" - 18 | 100      | 0.22                 | 22.0                |
| AI 3-WBA       | 7             | 3"               | 5/16" - 18 | 25       | 0.24                 | 6.0                 |
| AI 3 1/2-WBA   | 8             | 3-1/2"           | 5/16" - 18 | 50       | 0.32                 | 16.0                |
| AI 4-WBA       | 9             | 4"               | 5/16" - 18 | 25       | 0.48                 | 12.0                |

## Beam Clamps - Malleable Iron

### Industry Standards

- UL 2239

### Construction

- Malleable Iron with Zinc Plating
- Steel Bolt

### Application

- Used to hang or provide mounting means for the attachment of conduit hangers
- For structural attachment to top or bottom of metal beams, purlins, channel, or angle iron

### Features

- For load capacities from 75 to 450 lbs



| catalog number | size in inches | jaw opening | box qty. | weight lbs. per unit | weight lbs. per box | hole size |
|----------------|----------------|-------------|----------|----------------------|---------------------|-----------|
| AI MBC-1420    | 1"             | 3/4"        | 50       | 0.24                 | 12.0                | 1/4"      |
| AI MBC-3816    | 2"             | 7/8"        | 25       | 0.53                 | 13.2                | 3/8"      |
| AI MBC-1213A   | 2-1/2"         | 1-1/4"      | 20       | 1.17                 | 23.4                | 1/2"      |