

## Two Hole EMT Strap - Snap On

### Industry Standards

- UL 2239

### Construction


- Steel with Zinc Plating

### Application

- Provides support to conduit where higher load bearing supports are required

### Features

- High corrosion resistance
- Inverted rib for additional strength



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI 1124	½"	50	0.020	1.0	2.21	0.58
AI 1125	¾"	50	0.030	1.5	2.68	0.63
AI 1126	1"	50	0.040	2.0	2.98	0.76
AI 1127	1¼"	20	0.060	1.2	3.69	0.89
AI 1128	1½"	20	0.080	1.6	4.23	1.00
AI 1129	2"	50	0.140	7.0	4.92	1.11

## Conduit Hanger with Nut and Bolt

### Industry Standards

- UL 2239

### Construction

- Steel with Zinc Plating

### Application

- To secure and suspend conduit (Rigid, IMC, EMT or PVC) from overhead support

### Features

- High corrosion resistance
- Furnished with carriage bolt



catalog number	industry size	For EMT Diameter	bolt size	box qty.	weight lbs. per unit	weight lbs. per box
AI 1/2-WBA	0	½"	¼" - 20	100	0.06	6.0
AI 3/4-WBA	1	¾"	¼" - 20	100	0.08	8.0
AI 1-WBA	2	1"	¼" - 20	100	0.09	9.0
AI 1 1/4-WBA	2½	1¼"	½" - 20	100	0.10	10.0
AI 1 1/2-WBA	3	1½"	¼" - 20	100	0.10	10.0
AI 2-WBA	5	2"	½" - 20	50	0.20	10.0
AI 2 1/2-WBA	6	2½"	⁵⁄₁₆" - 18	100	0.22	22.0
AI 3-WBA	7	3"	⁵⁄₁₆" - 18	25	0.24	6.0
AI 3 1/2-WBA	8	3½"	⁵⁄₁₆" - 18	50	0.32	16.0
AI 4-WBA	9	4"	⁵⁄₁₆" - 18	25	0.48	12.0

## Beam Clamps - Malleable Iron

### Industry Standards

- UL 2239

### Construction

- Malleable Iron with Zinc Plating
- Steel Bolt

### Application

- Used to hang or provide mounting means for the attachment of conduit hangers
- For structural attachment to top or bottom of metal beams, purlins, channel, or angle iron

### Features

- For load capacities from 75 to 450 lbs



catalog number	size in inches	jaw opening	box qty.	weight lbs. per unit	weight lbs. per box	hole size
AI MBC-1420	1"	¾"	50	0.24	12.0	¼"
AI MBC-3816	2"	⁷⁄₈"	25	0.53	13.2	⅜"
AI MBC-1213A	2½"	1¼"	20	1.17	23.4	½"