

EMT Elbow - 45°

Industry Standards

- UL 797

Construction


- Reduced Wall Galvanized Steel

Application

- For use in joining or enabling bends in EMT conduit when required for correct alignment

Features

- High corrosion resistance
- Low conductivity
- Smooth interior and exterior for easier wire pulling



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI ELE 50-45	½"	50	0.176	8.80	6.530	4.000
AI ELE 75-45	¾"	50	0.329	16.45	7.125	4.500
AI ELE 100-45	1"	25	0.637	15.93	8.561	5.750
AI ELE 125-45	1¼"	20	0.861	17.22	10.751	7.250
AI ELE 150-45	1½"	15	1.233	18.50	11.502	8.250
AI ELE 200-45	2"	10	1.872	18.72	12.440	9.500
AI ELE 250-45	2½"	1	3.971	3.97	13.561	10.500
AI ELE 300-45	3"	1	5.514	5.51	15.752	13.000
AI ELE 350-45	3½"	1	8.154	8.15	17.503	15.000
AI ELE 400-45	4"	1	9.481	9.48	18.501	16.000

EMT Elbow - 90° - Reduced Wall

Industry Standards

- UL 797

Construction


- Reduced Wall Galvanized Steel

Application

- For use in joining or enabling bends in EMT conduit when required for correct alignment

Features

- High corrosion resistance
- Low conductivity
- Smooth interior and exterior for easier wire pulling



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)		
					A	B	C
AI ELE 50-90	½"	50	0.265	13.25	6.375	6.375	4.25
AI ELE 75-90	¾"	50	0.486	24.30	7.501	7.501	4.50
AI ELE 100-90	1"	25	0.880	22.00	9.499	9.499	6.00
AI ELE 125-90	1¼"	20	1.541	30.82	11.251	11.251	8.00
AI ELE 150-90	1½"	15	1.982	29.73	13.001	13.001	9.13
AI ELE 200-90	2"	10	2.863	28.63	16.003	16.003	11.50
AI ELE 250-90	2½"	1	4.851	4.85	18.502	18.502	11.75
AI ELE 300-90	3"	1	6.831	6.83	22.251	22.251	14.25
AI ELE 350-90	3½"	1	10.143	10.14	25.000	25.000	17.00
AI ELE 400-90	4"	1	13.224	13.22	26.000	26.000	18.00