

Rigid Nipples - Threaded



Industry Standards

- UL 6
- Fed. Spec. WW-C 563

Construction

- Steel with Zinc Plated finish

Application

- For use in lengthening or ensuring correct alignment of two lengths of threaded Rigid and IMC

Features

- Tapered NPT Threading

catalog number	conduit size inches	length in inches	box qty.	weight lbs. per unit	weight lbs. per box
AI N 50- CL	½"	CLOSE	25	0.06	1.5
AI N 50- 150	½"	1½"	25	0.08	2
AI N 50- 200	½"	2"	25	0.12	3
AI N 50- 250	½"	2½"	25	0.15	3.75
AI N 50- 300	½"	3"	25	0.26	6.5
AI N 50- 350	½"	3½"	25	0.26	6.5
AI N 50- 400	½"	4"	25	0.26	6.5
AI N 50- 500	½"	5"	25	0.33	8.25
AI N 50- 600	½"	6"	25	0.4	10
AI N 50- 800	½"	8"	25	0.54	13.5
AI N 50-1000	½"	10"	25	0.68	17
AI N 50-1200	½"	12"	25	0.82	20.5
AI N 75- CL	¾"	CLOSE	25	0.09	2.25
AI N 75- 200	¾"	2"	25	0.14	3.5
AI N 75- 250	¾"	2½"	25	0.19	4.75
AI N 75- 300	¾"	3"	25	0.26	6.5
AI N 75- 350	¾"	3½"	25	0.28	7
AI N 75- 400	¾"	4"	25	0.33	8.25
AI N 75- 500	¾"	5"	25	0.42	10.5
AI N 75- 600	¾"	6"	25	0.52	13
AI N 75- 800	¾"	8"	25	0.73	18.25
AI N 75-1000	¾"	10"	25	0.89	22.25
AI N 75-1200	¾"	12"	25	1.09	27.25

catalog number	conduit size inches	length in inches	box qty.	weight lbs. per unit	weight lbs. per box
AI N100- CL	1"	CLOSE	25	0.16	4
AI N100- 200	1"	2"	25	0.22	5.5
AI N100- 250	1"	2½"	25	0.28	7
AI N100- 300	1"	3"	25	0.26	6.5
AI N100- 350	1"	3½"	25	0.42	10.5
AI N100- 400	1"	4"	25	0.48	12
AI N100- 500	1"	5"	25	0.63	15.75
AI N100- 600	1"	6"	25	0.8	20
AI N100- 800	1"	8"	25	1	25
AI N100-1000	1"	10"	25	1.11	27.75
AI N100-1200	1"	12"	25	2.01	50.25
AI N125- CL	1¼"	CLOSE	25	0.22	5.5
AI N125- 200	1¼"	2"	25	0.28	7
AI N125- 250	1¼"	2½"	25	0.37	9.25
AI N125- 300	1¼"	3"	25	0.37	9.25
AI N125- 350	1¼"	3½"	25	0.48	12
AI N125- 400	1¼"	4"	25	0.56	14
AI N125- 500	1¼"	5"	25	0.68	17
AI N125- 600	1¼"	6"	25	0.84	21
AI N125- 800	1¼"	8"	25	1.01	25.25
AI N125-1000	1¼"	10"	25	1.02	25.5
AI N125-1200	1¼"	12"	25	2.01	50.25

Rigid Nipple - Threaded



Industry Standards

- UL 6
- Fed. Spec. WW-C 563

Construction

- Steel with Zinc Plated finish

Application

- For use in lengthening or ensuring correct alignment of two lengths of threaded Rigid and IMC

Features

- Tapered NPT Threading

catalog number	conduit size inches	length in inches	box qty.	weight lbs. per unit	weight lbs. per box
AI N150- CL	1½"	CLOSE	25	0.28	7
AI N150- 200	1½"	2"	25	0.34	8.5
AI N150- 250	1½"	2½"	25	0.44	11
AI N150- 300	1½"	3"	25	0.56	14
AI N150- 350	1½"	3½"	25	0.68	17
AI N150- 400	1½"	4"	25	0.8	20
AI N150- 500	1½"	5"	25	1.03	25.75
AI N150- 600	1½"	6"	25	1.24	31
AI N150- 800	1½"	8"	25	1.9	47.5
AI N150-1000	1½"	10"	25	2.02	50.5
AI N150-1200	1½"	12"	25	3	75
AI N200- CL	2"	CLOSE	10	0.44	4.4
AI N200- 250	2"	2½"	10	0.6	6
AI N200- 300	2"	3"	10	0.72	7.2
AI N200- 350	2"	3½"	10	0.88	8.8
AI N200- 400	2"	4"	10	1.04	10.4
AI N200- 500	2"	5"	10	1.32	13.2
AI N200- 600	2"	6"	10	1.6	16
AI N200- 800	2"	8"	5	1.01	5.05
AI N200-1000	2"	10"	5	2.9	14.5
AI N200-1200	2"	12"	5	3.05	15.25
AI N250- CL	2½"	CLOSE	10	0.98	9.8
AI N250- 300	2½"	3"	10	1.04	10.4
AI N250- 350	2½"	3½"	10	2	20
AI N250- 400	2½"	4"	10	2.11	21.1
AI N250- 500	2½"	5"	10	3	30
AI N250- 600	2½"	6"	10	3.25	32.5
AI N250- 800	2½"	8"	5	3.89	19.45
AI N250-1000	2½"	10"	5	4.86	24.3
AI N250-1200	2½"	12"	5	5.91	29.55

catalog number	conduit size inches	length in inches	box qty.	weight lbs. per unit	weight lbs. per box
AI N300- CL	3"	CLOSE	10	1.025	10.25
AI N300- 300	3"	3"	10	1.11	11.1
AI N300- 350	3"	3½"	10	1.97	19.7
AI N300- 400	3"	4"	10	2.04	20.4
AI N300- 500	3"	5"	10	3.02	30.2
AI N300- 600	3"	6"	5	3.15	15.75
AI N300- 800	3"	8"	5	3.99	19.95
AI N300-1000	3"	10"	5	4.83	24.15
AI N300-1200	3"	12"	5	5.92	29.6
AI N350- CL	3½"	CLOSE	6	1.98	11.88
AI N350- 400	3½"	4"	6	2.14	12.84
AI N350- 500	3½"	5"	6	2.91	17.46
AI N350- 600	3½"	6"	5	3.87	19.35
AI N350- 800	3½"	8"	3	4.92	14.76
AI N350-1000	3½"	10"	3	6.88	20.64
AI N350-1200	3½"	12"	3	7.91	23.73
AI N400- CL	4"	CLOSE	6	1.99	11.94
AI N400- 400	4"	4"	6	2.87	17.22
AI N400- 500	4"	5"	6	3.86	23.16
AI N400- 600	4"	6"	4	4.19	16.76
AI N400- 800	4"	8"	3	5.91	17.73
AI N400-1000	4"	10"	3	7.92	23.76
AI N400-1200	4"	12"	3	8.78	26.34