

Bushed Nipples

Industry Standards

- UL 514B
- Fed. Spec. W-F-408E
- NEMA FB-1

Construction


- Malleable Iron with Zinc Plated finish

Application

- For use with a locknut to connect between two boxes side by side or back to back
- For use with a locknut to connect fixture housing to continuous runs
- For use through knockout to connect box to conduit coupling

Features

- NPSM Threading for Rigid Conduit and IMC
- RoHS compliant



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI MCN- 50	1/2"	50	0.06	3.0	0.69	1.03
AI MCN- 75	3/4"	50	0.08	4.0	0.76	1.31
AI MCN-100	1"	25	0.15	3.7	0.88	1.54
AI MCN-125	1-1/4"	20	0.24	4.8	0.93	1.9
AI MCN-150	1-1/2"	15	0.29	4.4	0.95	2.31
AI MCN-200	2"	25	0.38	9.4	1.08	2.89
AI MCN-250	2-1/2"	20	0.71	14.1	1.39	3.4
AI MCN-300	3"	10	1.24	12.4	1.45	4.07
AI MCN-350	3-1/2"	10	1.63	16.3	1.48	4.62
AI MCN-400	4"	10	1.98	19.8	1.48	5.14

Bushed Nipples - Insulated Throat

Industry Standards

- UL 514B
- Fed. Spec. W-F-408E
- NEMA FB-1

Construction


- Malleable Iron with Zinc Plated finish

Application

- For use with a locknut to connect between two boxes side by side or back to back
- For use with a locknut to connect fixture housing to continuous runs
- For use through knockout to connect box to conduit coupling

Features

- NPSM Threading for Rigid Conduit and IMC
- RoHS compliant



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI MCN- 50I	1/2"	50	0.06	3.0	0.69	1.05
AI MCN- 75I	3/4"	50	0.08	4.0	1.01	1.31
AI MCN-100I	1"	25	0.15	3.7	0.89	1.54
AI MCN-125I	1-1/4"	20	0.24	4.8	0.96	1.91
AI MCN-150I	1-1/2"	15	0.29	4.4	0.93	2.31
AI MCN-200I	2"	25	0.38	9.4	1.08	2.89
AI MCN-250I	2-1/2"	20	0.71	14.1	1.39	3.41
AI MCN-300I	3"	10	1.24	12.4	1.46	4.09
AI MCN-350I	3-1/2"	10	1.63	16.3	1.49	4.63
AI MCN-400I	4"	10	1.98	19.8	1.49	5.17

Rigid Conduit Couplings - Threaded

Industry Standards

- UL 6
- Fed. Spec. WW-C 563

Construction

- Steel with Zinc Plated finish

Application

- For use in joining or ensuring correct alignment of two lengths of threaded Rigid and IMC

Features

- Straight Threads
- For Indoor or Outdoor use



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI RC 050	1/2"	100	0.13	13.0	1.001	1.626
AI RC 075	3/4"	50	0.16	8.0	1.250	1.626
AI RC 100	1"	30	0.28	8.3	1.500	2.001
AI RC 125	1-1/4"	25	0.33	8.3	1.875	2.064
AI RC 150	1-1/2"	25	0.44	11.0	2.125	2.126
AI RC 200	2"	20	0.71	14.2	2.625	2.187
AI RC 250	2-1/2"	24	1.70	40.8	3.187	3.187
AI RC 300	3"	16	2.05	32.8	3.812	3.125
AI RC 350	3-1/2"	12	2.65	31.8	4.501	3.439
AI RC 400	4"	10	3.48	34.8	4.812	3.501
AI RC 500	5"	1	4.41	4.4	6.001	3.937
AI RC 600	6"	1	7.39	7.4	7.126	4.313