


One Hole EMT Strap - Snap On



Industry Standards

- UL 2239

Construction

- Steel with Zinc Plating

Application


- Provides support to conduit as required by the NEC

Features

- High corrosion resistance
- Inverted rib for additional strength

catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI 1701	1/2"	100	0.025	2.5	1.80	0.58
AI 1702	3/4"	100	0.030	3.0	1.97	0.63
AI 1703	1"	50	0.050	2.5	2.26	0.76
AI 1704	1 1/4"	25	0.080	2.0	2.87	0.89
AI 1705	1 1/2"	25	0.120	3.0	3.18	1.00
AI 1706	2"	25	0.160	4.0	3.95	1.11

Two Hole EMT Strap - Snap On



Industry Standards

- UL 2239

Construction

- Steel with Zinc Plating

Application

- Provides support to conduit where higher load bearing supports are required

Features

- High corrosion resistance
- Inverted rib for additional strength

catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI 1124	1/2"	50	0.020	1.0	2.21	0.58
AI 1125	3/4"	50	0.030	1.5	2.68	0.63
AI 1126	1"	50	0.040	2.0	2.98	0.76
AI 1127	1 1/4"	20	0.060	1.2	3.69	0.89
AI 1128	1 1/2"	20	0.080	1.6	4.23	1.00
AI 1129	2"	50	0.140	7.0	4.92	1.11

One-Hole Strap for Rigid Conduit - Malleable Iron



Industry Standards

- UL 2239

Construction

- Malleable iron with zinc plated finish

Application

- Indoor or outdoor usage
- Used to secure Rigid conduit or IMC where load bearing is required

Features

- Heavy Duty Casting
- RoHS compliant

catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI MST- 38	3/8"	25	0.04	1.0	1.39	0.56
AI MST- 50	1/2"	25	0.062	1.6	1.44	0.63
AI MST- 75	3/4"	20	0.075	1.5	1.75	0.76
AI MST-100	1"	10	0.092	0.9	1.88	0.88
AI MST-125	1 1/4"	30	0.217	6.5	2.38	1.01
AI MST-150	1 1/2"	25	0.318	8.0	2.75	1.25
AI MST-200	2"	15	0.442	6.6	3.28	1.38
AI MST-250	2 1/2"	10	0.663	6.6	3.28	1.38
AI MST-300	3"	2	1.032	2.1	4.19	1.76
AI MST-350	3 1/2"	3	1.85	5.6	5.49	2.13
AI MST-400	4"	2	2.21	4.4	6.51	2.25