

## One-Hole Strap for Rigid Conduit - Steel



### Construction

- Steel with Zinc Plated finish

### Application


- Indoor or outdoor usage
- Used to secure Rigid conduit or IMC where load bearing is required

### Features

- Easily installed on wood and masonry

catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI 699	1/4"	50	0.02	1.0	1.52	0.563
AI 700	3/8"	100	0.03	3.0	1.20	0.54
AI 701	1/2"	50	0.04	2.1	1.92	0.625
AI 702	3/4"	50	0.07	3.5	2.22	0.751
AI 703	1"	25	0.10	2.5	2.57	1.125
AI 704	1 1/4"	20	0.13	2.6	2.80	1.131
AI 705	1 1/2"	10	0.16	1.6	3.71	1.15
AI 706	2"	50	0.22	11.0	4.16	1.391
AI 707	2 1/2"	10	0.42	4.2	5.01	1.531
AI 708	3"	5	0.52	2.6	5.56	1.531
AI 709	3 1/2"	5	0.72	3.6	6.38	1.531
AI 710	4"	5	0.80	4.0	6.88	1.531

## Two-Hole Strap for Rigid Conduit - Steel



### Construction

- Steel with Zinc Plated finish

### Application


- Indoor or outdoor usage
- Used to secure Rigid conduit or IMC where load bearing is required

### Features

- Easily installed on wood and masonry

catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI 124	1/2"	50	0.090	4.5	2.47	0.89
AI 125	3/4"	50	0.110	5.5	2.87	1.26
AI 126	1"	25	0.140	3.5	3.33	1.54
AI 127	1 1/4"	20	0.281	5.6	4.18	1.72
AI 128	1 1/2"	10	0.461	4.6	4.45	2.0
AI 129	2"	50	0.552	27.6	5.07	2.83
AI 130	2 1/2"	10	0.725	7.3	5.76	3.04
AI 131	3"	5	1.610	8.1	6.25	3.68
AI 132	3 1/2"	5	2.480	12.4	7.06	4.45
AI 133	4"	5	3.310	16.6	8.18	4.89

## Two-Hole Strap for Conduit - PVC



### Construction

- Polyvinyl Chloride

### Application

- Used to support anchor conduit to interior or exterior surfaces
- Ideal for handling the additional thickness of PVC conduit

### Features

- Schedule 40 rated PVC
- U-Shaped, two hole strap design to ensure additional load bearing capacity
- Can be installed with nails or screws
- Weather resistant and can be installed both indoor and outdoor

catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI PS 050	1/2"	100	0.006	0.6	2.1	1.0
AI PS 075	3/4"	100	0.010	1.0	2.38	1.25
AI PS 100	1"	100	0.010	1.0	2.75	1.5
AI PS 125	1 1/4"	50	0.015	0.8	3.1	1.8
AI PS 150	1 1/2"	25	0.020	0.5	3.25	2.13
AI PS 200	2"	25	0.030	0.8	4.13	2.5
AI PS 250	2 1/2"	1	0.070	0.1	5.88	2.88
AI PS 300	3"	1	0.080	0.1	5.88	3.63
AI PS 400	4"	1	0.090	0.1	8.00	4.25