

## Beam Clamps -Steel

### Industry Standards

- UL 2239

### Construction

- Steel with Zinc Plating
- Steel Bolt



### Application

- Used to provide mounting means for the attachment of conduit hangers either directly or by means of threaded rod
- For structural attachment to top or bottom of metal beams, purlins, channel, or angle iron

### Features

- For load capacities from 75 to 200 lbs

catalog number	size in inches	jaw opening	max. weight load	box qty.	weight lbs. per unit	weight lbs. per box
AI BC 16	3/8" - 16	7/8"	200 Lbs.	25	0.200	5.0
AI BC 20	1/4" - 20	3/4"	75 Lbs.	50	0.220	11.0

## Rigid/EMT Clamp Backs

### Industry Standards

- UL 2239

### Construction


- Malleable Iron with Zinc Plating

### Application

- Provides desired spacing between mounting surface and for conduit runs
- For Indoor and Outdoor use

### Features

- Solid, malleable iron body will not distort due to environmental conditions



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)		
					A	B	C
AI MCB- 50	1/2"	50	0.06	3.2	2.07	1.00	0.51
AI MCB- 75	3/4"	50	0.09	4.4	2.39	1.06	0.51
AI MCB-100	1"	25	0.14	3.5	2.95	1.25	0.57
AI MCB-125	1-1/4"	25	0.21	5.3	3.51	1.88	0.76
AI MCB-150	1-1/2"	15	0.27	4.1	3.82	1.44	0.82
AI MCB-200	2"	25	0.44	11.0	4.76	1.94	0.87
AI MCB-250	2-1/2"	25	0.56	14.0	5.76	2.44	0.88
AI MCB-300	3"	25	0.90	22.5	6.7	2.63	0.89
AI MCB-350	3-1/2"	10	1.40	14.0	7.13	2.89	1.06
AI MCB-400	4"	10	1.80	18.0	8.89	3.07	1.06

## Rigid/EMT Nail Straps

### Construction


- Stamped Steel

### Application

- Designed to secure Rigid, IMC or EMT to wooden surfaces

### Features

- Higher tensile strength and withstands a higher striking force



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)		
					A	B	C
AI 1600	1/2"	100	0.025	2.5	1.813	1.063	0.25
AI 1605	3/4"	100	0.032	3.2	2.001	1.25	0.25
AI 1615	1"	100	0.044	4.4	2.501	1.5	0.25