

Small 2Gen LED Slimline Wall Pack - AI TV2C32X10U41KZ & AI TV2C32X20U41KZ



L70
25°C **76,000 Hours**

Description


The Atlantic Industrial AI TV2C3 cut-off wall mounted luminaire is available in two wattages designed to replace HID lighting systems up to 175w MH or HPS. Typical wall mounted lighting applications include retail centers, industrial parks, schools and universities, public transit and airports, office buildings and medical facilities. Mounting heights of 8 to 15 feet can be used based on light level and uniformity requirements.

Specifications and Features

- **Delivered Lumens:** 2,300 (20w); 4,100 (40w)
- **Housing:** Die-cast gasketed aluminum housing, includes cast-in box template and built in level. White reflector. Nickel-plated stainless steel hardware.
- **Finish:** Textured architectural bronze powdercoat finish over a chromate conversion coating.
- **Lens:** Tempered clear flat glass lens.
- **Mounting Options:** Mount directly over recessed electrical box or use 1/2" surface conduit.
- **COB LED:** Cool Copper COB
- **Wattage:** 20w COB: 20w, System: 21w (100w HID equivalent); 40w COB: 40w, System: 43w; (175w HID equivalent)
- **Driver:** Electronic driver, 120-277V, 50/60Hz; dimmable driver
- **Listing & Ratings:** CSA: Listed for wet locations. Operating temperatures: -40°C to +50°C. IP66



A height	B length	D width
7 7/8"	4 1/2"	6 5/8"
200mm	114mm	168mm



Large 2Gen LED Slimline Wall Pack - AI TV3C34X15U41KZ & AI TV3C34X20U41KZ



L70
25°C **77,000 Hours**

Description

The Atlantic Industrial AI TV3C3 cut-off wall mounted luminaire is available in two wattages designed to replace HID lighting systems up to 400w MH or HPS. Typical wall mounted lighting applications include retail centers, industrial parks, schools and universities, public transit and airports, office buildings and medical facilities. Mounting heights of 12 to 20 feet can be used based on light level and uniformity requirements.

Specifications and Features

- **Delivered Lumens:** 6,600 (60w); 8,300 (80w)
- **Housing:** Die-cast gasketed aluminum housing, includes cast-in box template and built in level. White reflector. Nickel-plated stainless steel hardware.
- **Finish:** Textured architectural bronze powdercoat finish over a chromate conversion coating.
- **Lens:** Tempered clear flat glass lens.
- **Mounting Options:** Mount directly over recessed electrical box or use 1/2" surface conduit.
- **COB LED:** Cool Copper COB
- **Wattage:** 60w COB: 60w, System: 56w; (250w HID equivalent) 80w COB: 80w, System: 80w; (400w HID equivalent)
- **Driver:** Electronic driver, 120-277V, 50/60Hz; dimmable driver
- **Listing & Ratings:** CSA: Listed for wet locations. Operating temperatures: -40°C to +50°C. IP66



A height	B length	D width
11 1/4"	6 1/2"	9 3/4"
286mm	156mm	248mm

