

## Compression Type Connectors - Threadless

### Industry Standards

- UL 514B
- Fed. Spec. W-F-408E
- NEMA FB-1

### Construction

- Malleable iron with zinc plated finish

### Application

- For use in joining threadless Rigid and IMC to steel outlet box or metal enclosures

### Features

- Compression type unthreaded connector
- Concrete tight male hub threads when taped



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI MCC- 50	½"	25	0.24	6.0	1.36	1.17
AI MCC- 75	¾"	20	0.25	5.0	1.49	1.43
AI MCC-100	1"	10	0.39	3.9	1.59	1.76
AI MCC-125	1¼"	30	0.59	17.7	1.87	2.16
AI MCC-150	1½"	20	0.72	14.4	1.95	2.39
AI MCC-200	2"	15	1.2	18.0	2.48	3.39
AI MCC-250	2½"	10	2.9	29.0	3.01	3.76
AI MCC-300	3"	4	3.28	13.12	3.126	4.26
AI MCC-350	3½"	2	3.42	6.84	3.188	4.75
AI MCC-400	4"	2	4.7	9.4	3.438	5.31

## Compression Type Connectors - Threadless with Insulated Throat

### Industry Standards

- UL 514B
- Fed. Spec. W-F-408E
- NEMA FB-1

### Construction


- Malleable iron with zinc plated finish

### Application

- For use in joining threadless Rigid and IMC to steel outlet box or metal enclosures

### Features

- Compression type unthreaded connector
- Concrete tight male hub threads when taped



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI MCC- 50I	½"	25	0.24	6.0	1.35	1.17
AI MCC- 75I	¾"	20	0.26	5.2	1.48	1.43
AI MCC-100I	1"	10	0.40	4.0	1.58	1.75
AI MCC-125I	1¼"	30	0.59	17.7	1.86	2.15
AI MCC-150I	1½"	20	0.74	14.8	1.94	2.38
AI MCC-200I	2"	15	1.20	18.0	2.48	3.38
AI MCC-250I	2½"	10	2.90	29.0	3.00	3.75
AI MCC-300I	3"	4	3.30	13.2	3.125	4.25
AI MCC-350I	3½"	2	3.50	7.0	3.187	4.75
AI MCC-400I	4"	2	4.8	9.6	3.438	5.31

## Compression Type Couplings - Threadless

### Industry Standards

- UL 514B
- Fed. Spec. W-F-408E
- NEMA FB-1

### Construction


- Malleable iron with zinc plated finish

### Application

- For use in joining two lengths of threadless Rigid and IMC

### Features

- Compression type unthreaded coupling
- Concrete tight male hub threads when taped



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI MCP- 50	½"	15	0.30	4.5	1.80	1.17
AI MCP- 75	¾"	10	0.32	3.2	1.88	1.43
AI MCP-100	1"	5	0.44	2.2	2.19	1.75
AI MCP-125	1¼"	25	0.78	19.4	1.63	2.15
AI MCP-150	1½"	15	0.93	14.0	2.69	2.38
AI MCP-200	2"	8	1.59	12.7	3.06	3.38
AI MCP-250	2½"	3	2.70	8.1	4.50	3.75
AI MCP-300	3"	3	3.57	10.7	4.94	4.25
AI MCP-350	3½"	3	4.47	13.4	5.00	4.75
AI MCP-400	4"	2	5.76	11.5	5.31	5.31