

## One-Hole Strap for Rigid Conduit - Malleable Iron



### Industry Standards

- UL 2239

### Construction

- Malleable iron with zinc plated finish

### Application

- Indoor or outdoor usage
- Used to secure Rigid conduit or IMC where load bearing is required

### Features

- Heavy Duty Casting
- RoHS compliant

catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box
AI MST- 38	3/8"	25	0.04	1.0
AI MST- 50	1/2"	25	0.062	1.6
AI MST- 75	3/4"	20	0.075	1.5
AI MST-100	1"	10	0.092	0.9
AI MST-125	1 1/4"	30	0.217	6.5
AI MST-150	1 1/2"	25	0.318	8.0
AI MST-200	2"	15	0.442	6.6
AI MST-250	2 1/2"	10	0.663	6.6
AI MST-300	3"	2	1.032	2.1
AI MST-350	3 1/2"	3	1.85	5.6
AI MST-400	4"	2	2.21	4.4

## One-Hole Strap for Rigid Conduit - Steel



### Construction

- Steel with Zinc Plated finish

### Application

- Indoor or outdoor usage
- Used to secure Rigid conduit or IMC where load bearing is required

### Features

- Easily installed on wood and masonry

catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box
AI 699	1/4"	50	0.02	1.0
AI 700	3/8"	50	0.03	1.5
AI 701	1/2"	50	0.04	2.1
AI 702	3/4"	50	0.07	3.5
AI 703	1"	25	0.10	2.5
AI 704	1 1/4"	20	0.13	2.6
AI 705	1 1/2"	10	0.16	1.6
AI 706	2"	50	0.22	11.0
AI 707	2 1/2"	10	0.42	4.2
AI 708	3"	5	0.52	2.6
AI 709	3 1/2"	5	0.72	3.6
AI 710	4"	5	0.80	4.0

## Two-Hole Strap for Rigid Conduit - Steel



### Construction

- Steel with Zinc Plated finish

### Application

- Indoor or outdoor usage
- Used to secure Rigid conduit or IMC where load bearing is required

### Features

- Easily installed on wood and masonry

catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box
AI 124	1/2"	50	0.090	4.5
AI 125	3/4"	50	0.110	5.5
AI 126	1"	25	0.140	3.5
AI 127	1 1/4"	20	0.281	5.6
AI 128	1 1/2"	10	0.461	4.6
AI 129	2"	50	0.552	27.6
AI 130	2 1/2"	10	0.725	7.3
AI 131	3"	5	1.610	8.1
AI 132	3 1/2"	5	2.480	12.4
AI 133	4"	5	3.310	16.6