

## Rigid Conduit Nipples 1/2" to 2-1/2"

### Industry Standards

- UL 6
- Fed. Spec. WW-C 563

### Construction

- Steel with Zinc Plated finish

### Application

- For use in lengthening or ensuring correct alignment of two lengths of threaded Rigid and IMC

### Features

- NPT Threading



catalog number	conduit size inches	length in inches	box qty.	weight lbs. per unit	weight lbs. per box
AI N 50- CL	1/2"	CLOSE	25	0.06	1.5
AI N 50- 150	1/2"	1-1/2"	25	0.08	2
AI N 50- 200	1/2"	2"	25	0.12	3
AI N 50- 250	1/2"	2-1/2"	25	0.15	3.75
AI N 50- 300	1/2"	3"	25	0.26	6.5
AI N 50- 350	1/2"	3-1/2"	25	0.26	6.5
AI N 50- 400	1/2"	4"	25	0.26	6.5
AI N 50- 500	1/2"	5"	25	0.33	8.25
AI N 50- 600	1/2"	6"	25	0.4	10
AI N 50- 800	1/2"	8"	25	0.54	13.5
AI N 50-1000	1/2"	10"	25	0.68	17
AI N 50-1200	1/2"	12"	25	0.82	20.5
AI N 75- CL	3/4"	CLOSE	25	0.09	2.25
AI N 75- 200	3/4"	2"	25	0.14	3.5
AI N 75- 250	3/4"	2-1/2"	25	0.19	4.75
AI N 75- 300	3/4"	3"	25	0.26	6.5
AI N 75- 350	3/4"	3-1/2"	25	0.28	7
AI N 75- 400	3/4"	4"	25	0.33	8.25
AI N 75- 500	3/4"	5"	25	0.42	10.5
AI N 75- 600	3/4"	6"	25	0.52	13
AI N 75- 800	3/4"	8"	25	0.73	18.25
AI N 75-1000	3/4"	10"	25	0.89	22.25
AI N 75-1200	3/4"	12"	25	1.09	27.25
AI N100- CL	1"	CLOSE	25	0.16	4
AI N100- CL	1"	2"	25	0.22	5.5
AI N100- 150	1"	2-1/2"	25	0.28	7
AI N100- 200	1"	3"	25	0.26	6.5
AI N100- 350	1"	3-1/2"	25	0.42	10.5
AI N100- 400	1"	4"	25	0.48	12
AI N100- 500	1"	5"	25	0.63	15.75
AI N100- 600	1"	6"	25	0.8	20
AI N100- 800	1"	8"	25	1	25
AI N100-1000	1"	10"	25	1.11	27.75
AI N100-1200	1"	12"	25	2.01	50.25

catalog number	conduit size inches	length in inches	box qty.	weight lbs. per unit	weight lbs. per box
AI N125- CL	1-1/4"	CLOSE	25	0.22	5.5
AI N125- 200	1-1/4"	2"	25	0.28	7
AI N125- 250	1-1/4"	2-1/2"	25	0.37	9.25
AI N125- 300	1-1/4"	3"	25	0.37	9.25
AI N125- 350	1-1/4"	3-1/2"	25	0.48	12
AI N125- 400	1-1/4"	4"	25	0.56	14
AI N125- 500	1-1/4"	5"	25	0.68	17
AI N125- 600	1-1/4"	6"	25	0.84	21
AI N125- 800	1-1/4"	8"	25	1.01	25.25
AI N125-1000	1-1/4"	10"	25	1.02	25.5
AI N125-1200	1-1/4"	12"	25	2.01	50.25
AI N150- CL	1-1/2"	CLOSE	25	0.28	7
AI N150- 200	1-1/2"	2"	25	0.34	8.5
AI N150- 250	1-1/2"	2-1/2"	25	0.44	11
AI N150- 300	1-1/2"	3"	25	0.56	14
AI N150- 350	1-1/2"	3-1/2"	25	0.68	17
AI N150- 400	1-1/2"	4"	25	0.8	20
AI N150- 500	1-1/2"	5"	25	1.03	25.75
AI N150- 600	1-1/2"	6"	25	1.24	31
AI N150- 800	1-1/2"	8"	25	1.9	47.5
AI N150-1000	1-1/2"	10"	25	2.02	50.5
AI N150-1200	1-1/2"	12"	25	3	75
AI N200- CL	2"	CLOSE	10	0.44	4.4
AI N200- 250	2"	2-1/2"	10	0.6	6.0
AI N200- 300	2"	3"	10	0.72	7.2
AI N200- 350	2"	3-1/2"	10	0.88	8.8
AI N200- 400	2"	4"	10	1.04	10.4
AI N200- 500	2"	5"	10	1.32	13.2
AI N200- 600	2"	6"	10	1.6	16
AI N200- 800	2"	8"	5	1.01	5.05
AI N200-1000	2"	10"	5	2.9	12.5
AI N200-1200	2"	12"	5	3.05	15.3
AI N250- CL	2-1/2"	CLOSE	10	0.98	9.8
AI N250- 300	2-1/2"	3"	10	1.04	10.4
AI N250- 350	2-1/2"	3-1/2"	10	2	20
AI N250- 400	2-1/2"	4"	10	2.11	21.1
AI N250- 500	2-1/2"	5"	10	3	30
AI N250- 600	2-1/2"	6"	10	3.25	32.5
AI N250- 800	2-1/2"	8"	5	3.89	19.45
AI N250-1000	2-1/2"	10"	5	4.86	24.3
AI N250-1200	2-1/2"	12"	5	5.91	29.55