

Rigid Conduit Nipples 3" to 4"

Industry Standards

- UL 6
- Fed. Spec. WW-C 563

Construction

- Steel with Zinc Plated finish

Application

- For use in lengthening or ensuring correct alignment of two lengths of threaded Rigid and IMC

Features

- NPT Threading



catalog number	conduit size in	length in inches	box qty.	weight lbs. per unit	weight lbs. per box
AI N300- CL	3"	CLOSE	10	1.025	25.625
AI N300- 300	3"	3"	10	1.11	27.75
AI N300- 350	3"	3-1/2"	10	1.97	49.25
AI N300- 400	3"	4"	10	2.04	51.0
AI N300- 500	3"	5"	10	3.02	75.5
AI N300- 600	3"	6"	5	3.15	78.75
AI N300- 800	3"	8"	5	3.99	99.75
AI N300-1000	3"	10"	5	4.83	120.75
AI N300-1200	3"	12"	5	5.92	148.0
AI N350- CL	3-1/2"	CLOSE	6	1.98	49.5

catalog number	conduit size in	length in inches	box qty.	weight lbs. per unit	weight lbs. per box
AI N350- 400	3-1/2"	4"	25	2.14	53.5
AI N350- 500	3-1/2"	5"	25	2.91	72.75
AI N350- 600	3-1/2"	6"	25	3.87	96.75
AI N350- 800	3-1/2"	8"	25	4.92	123.0
AI N350-1000	3-1/2"	10"	25	6.88	172.0
AI N350-1200	3-1/2"	12"	25	7.91	197.75
AI N400- CL	4"	CLOSE	25	1.99	49.75
AI N400- 400	4"	4"	25	2.87	71.75
AI N400- 500	4"	5"	25	3.86	96.5
AI N400- 600	4"	6"	25	4.19	104.75
AI N400- 800	4"	8"	25	5.91	147.75
AI N400-1000	4"	10"	25	7.92	198.0
AI N400-1200	4"	12"	25	8.78	219.5

Rigid Elbow - 45°

Industry Standards

- UL 6
- Fed. Spec. WW-C 563

Construction


- Steel with Zinc Plated finish

Application

- For use in joining or enabling bends when required for correct alignment of threaded Rigid and IMC

Features

- NPT Threading
- Low conductivity, corrosion resistant smooth interior and exterior



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI ELR 50-45	1/2"	50	0.694	34.7	2.00	4.00
AI ELR 75-45	3/4"	50	1.024	51.2	2.00	4.00
AI ELR 100-45	1"	25	1.610	40.3	2.25	5.75
AI ELR 125-45	1-1/4"	20	2.360	47.2	2.80	7.25
AI ELR 150-45	1-1/2"	15	3.066	46.0	2.80	8.25
AI ELR 200-45	2"	10	4.694	46.9	2.80	9.50
AI ELR 250-45	2-1/2"	1	8.000	8.0	4.00	10.50
AI ELR 300-45	3"	1	13.010	13.0	5.00	13.00
AI ELR 350-45	3-1/2"	1	16.004	16.0	6.00	15.00
AI ELR 400-45	4"	1	21.011	21.0	6.75	16.00

Rigid Elbow - 90°

Industry Standards

- UL 6
- Fed. Spec. WW-C 563

Construction


- Steel with Zinc Plated finish

Application

- For use in joining or enabling bends when required for correct alignment of threaded Rigid and IMC

Features

- NPT Threading
- Low conductivity, corrosion resistant smooth interior and exterior



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI ELR 50-90	1/2"	50	0.762	38.10	2.00	4.00
AI ELR 75-90	3/4"	50	1.124	56.20	2.00	4.00
AI ELR 100-90	1"	25	1.970	49.25	2.25	5.75
AI ELR 125-90	1-1/4"	20	3.128	62.56	2.80	7.25
AI ELR 150-90	1-1/2"	15	4.400	44.00	2.80	8.25
AI ELR 200-90	2"	10	6.601	66.01	2.80	9.50
AI ELR 250-90	2-1/2"	1	11.801	11.80	4.00	10.50
AI ELR 300-90	3"	1	16.503	16.50	5.00	13.00
AI ELR 350-90	3-1/2"	1	27.000	27.00	6.00	15.00
AI ELR 400-90	4"	1	33.050	33.05	6.75	16.00