

Three Piece Couplings - Threadless

Industry Standards

- UL 514B
- Fed. Spec. W-F-408E
- NEMA FB-1

Construction


- Malleable iron with zinc plated finish

Application

- For use in joining two lengths of threaded Rigid and IMC

Features

- Couples conduit when conduit can not be turned
- Concrete tight
- Direct Burial Rated
- For Outdoor without tape
- RoHS Compliant



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI MTC- 50	1/2"	25	0.2	5.0	1.44	1.37
AI MTC- 75	3/4"	20	0.3	6.0	1.64	1.59
AI MTC-100	1"	10	0.46	4.6	1.83	1.89
AI MTC-125	1 1/4"	30	1.1	33.0	2.2	2.38
AI MTC-150	1 1/2"	25	1.47	36.75	2.32	2.84
AI MTC-200	2"	15	2.2	33.0	2.46	3.3
AI MTC-250	2 1/2"	10	3.7	37.0	2.54	4.04
AI MTC-300	3"	5	4.0	20.0	2.59	4.62
AI MTC-350	3 1/2"	3	5.8	17.4	2.66	5.37
AI MTC-400	4"	2	9.0	18.0	3.44	5.87

Rigid Conduit Couplings - Threaded

Industry Standards

- UL 6
- Fed. Spec. WW-C 563

Construction

- Steel with Zinc Plated finish

Application

- For use in joining or ensuring correct alignment of two lengths of threaded Rigid and IMC

Features

- Straight Threads
- For Indoor or Outdoor use



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI RC 050	1/2"	100	0.13	13.0	1.001	1.626
AI RC 075	3/4"	50	0.16	8.0	1.250	1.626
AI RC 100	1"	30	0.28	8.3	1.500	2.001
AI RC 125	1 1/4"	25	0.33	8.3	1.875	2.064
AI RC 150	1 1/2"	25	0.44	11.0	2.125	2.126
AI RC 200	2"	20	0.71	14.2	2.625	2.187
AI RC 250	2 1/2"	24	1.70	40.8	3.187	3.187
AI RC 300	3"	16	2.05	32.8	3.812	3.125
AI RC 350	3 1/2"	12	2.65	31.8	4.501	3.439
AI RC 400	4"	10	3.48	34.8	4.812	3.501
AI RC 500	5"	1	4.41	4.4	6.001	3.937
AI RC 600	6"	1	7.39	7.4	7.126	4.313