


Reducing Bushings

Construction

- Steel with zinc plating


Application

- For dry usage only
- Used to reduce entry size of a run with Rigid conduit or IMC



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI LRB- 2	¾"x½"	50	0.04	2.0	0.650	0.920
AI LRB- 3	1"x½"	50	0.12	6.0	0.715	1.125
AI LRB- 4	1"x¾"	50	0.06	3.0	0.715	1.125
AI LRB- 5	1¼"x½"	25	0.28	7.0	0.820	1.470
AI LRB- 6	1¼"x¾"	25	0.24	6.0	0.820	1.470
AI LRB- 7	1¼"x1"	25	0.16	4.0	0.820	1.470
AI LRB- 8	1½"x½"	25	0.40	10.0	0.850	1.700
AI LRB- 9	1½"x¾"	10	0.36	3.6	0.850	1.700
AI LRB-10	1½"x1"	10	0.28	2.8	0.850	1.700
AI LRB-11	1½"x1¼"	15	0.12	1.8	0.850	1.700
AI LRB-14	2"x1"	10	0.70	7.0	0.970	2.230
AI LRB-15	2"x1¼"	10	0.50	5.0	0.970	2.230
AI LRB-16	2"x1½"	10	0.40	4.0	0.970	2.230

Reducing Washers



Construction

- Steel with zinc plating

Application

- To be used in pairs to reduce entry size of knockout holes

Features

- Multiple sizes available for many applications

catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI MR- 2	¾"x½"	100	0.02	2	1.420	0.870
AI MR- 3	1"x½"	100	0.02	2	1.710	0.870
AI MR- 4	1"x¾"	100	0.02	2	1.710	1.060
AI MR- 5	1¼"x½"	100	0.04	4	2.080	0.870
AI MR- 6	1¼"x¾"	100	0.04	4	2.080	1.125
AI MR- 7	1¼"x1"	100	0.02	2	2.080	1.335
AI MR- 8	1½"x½"	100	0.04	4	2.635	0.870
AI MR- 9	1½"x¾"	100	0.08	8	2.635	1.060
AI MR-10	1½"x1"	100	0.08	8	2.635	1.335
AI MR-11	1½"x1¼"	100	0.04	4	2.635	1.690
AI MR-12	2"x½"	50	0.08	4	3.265	0.870
AI MR-13	2"x¾"	50	0.08	4	3.265	1.060
AI MR-14	2"x1"	50	0.08	4	3.265	1.335
AI MR-15	2"x1¼"	50	0.08	4	3.265	1.690
AI MR-16	2"x1½"	50	0.08	4	3.265	1.935
AI MR-17	2½"x½"	50	0.08	4	3.265	0.870
AI MR-18	2½"x¾"	50	0.08	4	3.265	1.060
AI MR-19	2½"x1"	50	0.08	4	3.265	1.370
AI MR-20	2½"x1¼"	50	0.08	4	3.265	1.750
AI MR-21	2½"x1½"	50	0.04	2	3.265	1.995
AI MR-22	2½"x2"	50	0.04	2	3.265	2.425
AI MR-23	3"x½"	50	0.24	12	4.490	0.870