

**Atlantic**  
INDUSTRIAL®  
A QSSI Company

**Ultra-Quiet  
Bath Vents**



**AI BFV80UQ**  
80 CFM



**AI BFV80LEDUQ**  
80 CFM  
LED Light




**AI BFV110UQ**  
110 CFM



**AI BFV110LEDUQ**  
110 CFM  
LED Light



**AI BFV150UQ**  
150 CFM



**AI BFV150LEDUQ**  
150 CFM  
LED Light

[www.atlanticind.net](http://www.atlanticind.net)

# Atlantic **Ultra-Quiet** INDUSTRIAL® Bath Vents

A QSSI Company

## Features:

- Totally enclosed permanently lubricated capacitor-driven motor rated for continuous operation.
- **Galvanized steel housing with sound-absorbing plated finish** resists humidity and changing attic temperatures.
- Large counter-balanced centrifugal blower for maximum **airflow and quiet operation.**
- Includes 4" and 6" duct adaptors.
- Contemporary spring-mount grille designs.
- Adjustable mounting brackets for easy installation.
- Built-in junction box for easy wiring.
- Dishwasher safe grille for easy cleaning.
- Housing dimensions: 12" x 12" x 7¼". Grille: 13¼" x 13¼"

## LED:

- State-of-the-art LED light produces 1200 lumens at just 12 watts of power, more than a 100-watt incandescent bulb.
- CCT: 4000K, CRI: >70, 30,000 hour rating.
- Special polycarbonate diffuser provides an even light distribution without LED hot spots.
- 3-year warranty on LED light and driver.

Model #	Airflow (CFM)	Light	Sound (dB/Sones)	Coverage (Sq. Ft.)
AI BFV80UQ	80	N/A	23.5 dB ~ 0.4 Sones	Up to 72
AI BFV80LEDUQ	80	12 watt LED	23.5 dB ~ 0.4 Sones	Up to 72
AI BFV110UQ	110	N/A	27.2 dB ~ 0.8 Sones	Up to 100
AI BFV110LEDUQ	110	12 watt LED	27.2 dB ~ 0.8 Sones	Up to 100
AI BFV150UQ	150	N/A	31.1 dB ~ 1.2 Sones	Up to 136
AI BFV150LEDUQ	150	12 watt LED	31.1 dB ~ 1.2 Sones	Up to 136

Distributed By: