

Strut Pipe Clamps

Construction


- Steel with Zinc Plating finish
- Steel Bolt with Hex Nut

Application

- Used to hang and support Rigid, IMC, EMT or Flexible conduit from strut channel

Features

- The product design with steel screw and captive nut, assures safe and tight fit into strut channel to secure conduit in place
- Zinc plated steel resists corrosion and rusting



catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI STC 050	½"	100	0.180	18	1.24	2.30
AI STC 075	¾"	100	0.209	20.9	1.24	2.46
AI STC 100	1"	100	0.231	23.1	1.24	2.68
AI STC 125	1¼"	100	0.258	25.8	1.24	3.21
AI STC 150	1½"	100	0.520	52	1.24	3.42
AI STC 200	2"	50	0.619	30.95	1.24	4.00
AI STC 250	2½"	50	0.641	32.05	1.24	5.00
AI STC 300	3"	25	0.720	18	1.24	5.55
AI STC 350	3½"	25	0.839	20.975	1.24	6.00
AI STC 400	4"	25	1.000	25	1.24	6.50

Strut Clamp Saddle Hangers

Industry Standards

- UL 2239

Construction

- Steel with Zinc Plating finish
- Steel Screw

Application

- Used to secure Rigid, IMC, EMT or Flexible conduit from overhead or wall mounted strut channel

Features

- The single-screw, tight clamping design assures a fast clamp action to strut channel and secures conduit to strut
- Zinc plated steel resists corrosion and rusting



catalog number	trade size	rigid or EMT conduit size	design load	box qty.	weight lbs. per unit	weight lbs. per box
AI SSH 050	½"	5/16"-½"	200 lbs.	100	0.142	14.2
AI SSH 075	¾"	¾"	300 lbs.	100	0.165	16.6
AI SSH 100	1"	1"	300 lbs.	100	0.245	24.6
AI SSH 125	1¼"	1¼"	400 lbs.	100	0.25	25.2
AI SSH 150	1½"	1½"	400 lbs.	100	0.255	25.6
AI SSH 200	2"	2"	400 lbs.	50	0.375	18.8
AI SSH 250	2½"	2½"	400 lbs.	50	0.45	22.5
AI SSH 300	3"	3"	400 lbs.	25	0.492	12.3
AI SSH 350	3½"	3½"	400 lbs.	25	0.57	14.25
AI SSH 400	4"	4"	400 lbs.	25	0.595	14.8

Beam Clamps - Malleable

Industry Standards


- UL 2239

Construction

- Malleable Iron with Zinc Plating
- Steel Bolt

Application

- Used to hang Rigid conduit or IMC
- For structural attachment to top or bottom of metal beams, purlins, channel, or angle iron



catalog number	size in inches	jaw opening	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)			
						A	B	C	D
AI MBC-1420	1"	¾"	50	0.24	12.0	1⅜"	1⅜"	1⅜"	¼"
AI MBC-3816	2"	7/8"	25	0.53	13.2	1⅜"	1⅜"	1⅜"	3/8"
AI MBC-1213A	2½"	1¼"	20	1.17	23.4	2¼"	2⅝"	2⅞"	½"

Features

- Solid, malleable iron body will not distort or slip off beam when tightened
- Manufactured with precision to optimize functionality and dependability; jaw openings range from ¾" to 1¼"
- For load capacities from 125 to 450 lbs.