

## Liquid Tight Component Type Connectors - PVC - 90°



### Industry Standards

- UL 514B
- C-UL 22.2

### Construction

- Polyvinyl Chloride

### Application


- To be used to bond Non-Metallic Liquid Tight to box or enclosure
- Meets UL and C-UL requirements for wet and dry locations

### Features

- Assures reliable and safe performance in wet and dry locations
- 90° design assists in protecting cables in direction changes and reduces install time

catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)		
					A	B	C
AI NMFA 038	3/8"	10	0.09	0.9	2.561	2.139	1.089
AI NMFA 050	1/2"	10	0.09	0.9	2.561	2.139	1.089
AI NMFA 075	3/4"	10	0.11	1.1	2.842	2.381	1.307
AI NMFA 100	1"	5	0.16	0.8	2.852	2.812	1.501
AI NMFA 125	1 1/4"	5	0.40	2.0	3.963	3.359	2.403
AI NMFA 150	1 1/2"	2	0.50	1.0	4.132	3.452	2.681
AI NMFA 200	2"	1	0.90	0.9	4.681	4.039	3.312

## Liquid Tight Component Type Connectors - PVC - Straight



### Industry Standards

- UL 514B
- C-UL 22.2

### Construction

- Polyvinyl Chloride

### Application


- To be used to bond Non-Metallic Liquid Tight to box or enclosure
- Meets UL and C-UL requirements for wet and dry locations

### Features

- Assures reliable and safe performance in wet and dry locations
- Design assists in protecting cables in direction changes and reduces install time

catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI NMFS 038	3/8"	25	0.07	1.8	2.0	1.09
AI NMFS 050	1/2"	10	0.07	0.7	2.0	1.09
AI NMFS 075	3/4"	10	0.08	0.8	2.03	1.3
AI NMFS 100	1"	5	0.24	1.2	2.25	1.5
AI NMFS 125	1 1/4"	5	0.24	1.2	2.0	2.4
AI NMFS 150	1 1/2"	2	0.70	1.4	2.25	2.68
AI NMFS 200	2"	2	0.95	1.9	2.5	3.31

## Liquid Tight Non-Metallic Cord Grips



### Industry Standards

- UL Approved
- Neoprene Gland

### Construction

- Nylon 6/6

### Application

- Connects box or enclosure with round cord

### Features

- Provides a liquid tight connection

catalog number	size in inches	box qty.	weight lbs. per unit	weight lbs. per box	dimensions (in.)	
					A	B
AI PCG 50	1/2"	50	0.03	1.50	1.53	0.93
AI PCG 75	3/4"	25	0.05	1.25	1.97	1.3